

# Kyocera KX12



## Technical Specifications: CDMA Talk and Standby Times

- Talk time: Up to 6.9 hours
- Standby time: Up to 220 hours

Times may vary based on user settings, feature use and network configuration.

## Battery Type:

- High-capacity (1800 mAh) lithium ion (LiIon) battery

## Vocoders:

- 13 Kbps (Purevoice) and EVRC

## Size:

- 4.33 in x 1.97 in x 1.02 in  
(110 mm x 50 mm x 26 mm)

## Weight:

- 4.62 ounces (131 grams)

## Operational Temperature:

- -22° to 140°F (-30° to 60°C)

Battery performance limited in temperatures below 32° F (0°C)

## Highlights

- Group calling functionality for personal and business activities.
- Enhanced dust and water resistance, scratch-resistant housing, and protective rubber over-molding
- Robust, front-ported speakerphone for improved sound quality
- Internal antenna for smaller, more rugged and compact design
- Dedicated contacts scroll, walkie-talkie, volume control, and speakerphone buttons
- High-capacity battery for longer calls

## Additional Features

- Voice-activated dialing, and polyphonic ringtones
  - Large 128x128 CSTN 65k display
  - Predictive text-input software for rapid text entry
  - Contact directory stores names, addresses and notes
  - Includes scheduler, calculator, alarm clock, stopwatch, tip calculator, countdown timer, and world clock
  - Wallpapers, screensavers, and games
  - Flashlight
  - Super-jack data connection
  - CDMA2000® 1X and E-911 capable\*
  - Multiple language support
  - BREW® 2.1 or Java™ capable\*
  - Web access with WAP 2.1 browser\*
- \*Depending on services available from your carrier.

## Accessories

- High-capacity lithium ion battery
- Portable and installed hands-free car kits
- Walkie-talkie headset
- Travel, vehicle, and spare-battery chargers
- Walkie-talkie Dispatch Station
- Premium and standard cases
- Desktop charging stand
- Belt clip
- Click 'n Go Universal Attachment System
- mobile PhoneTools® (software and cable)
- Phone sleeve, pouch, and lens overlays



Visit our Web site at [www.kyocera-wireless.com](http://www.kyocera-wireless.com)  
Kyocera Wireless Corp., 10300 Campus Point Drive, San Diego, CA 92121  
USA 1-800-349-4188, Outside USA 1-858-882-1410

©2006 Kyocera Wireless Corp., San Diego California, USA. All rights reserved. No reproduction in whole or in part is allowed without prior written approval. Kyocera is a registered trademark of Kyocera Corporation. The Genuine Accessories by Kyocera logo is a trademark of Kyocera Wireless Corp. CDMA2000 is a registered trademark of TTA USA. BREW is a registered trademark of QUALCOMM, Inc. Java is a trademark of Sun Microsystems, Inc. mobile PhoneTools is a registered trademark of BVPR Software. All other marks are held by their respective owners.

Features and specifications are subject to change without notice. Non-metric weights and measures are approximate. Not all products may be available in your area.

